
BREM GEAR ATF DEXRON IV

- HC-Synthetic Automatic Transmission Fluid
-

Recommendation*: DEXRON® VI

completely downward compatible with

- DEXRON® III G/H
- DEXRON® II D/E
- Aisin Warner AW-1
- Aisin Warner JWS 3324
- ATF Type 3.0 / Type 3.1
- Bentley P/N PY112995PA
- BMW/Mini ATF 3+
- BMW/Mini P/N 83 22 0 142 516
- BMW/Mini P/N 83 22 0 397 114
- BMW/Mini P/N 83 22 2 163 514 (BMW 8072 B)
- Chrysler/Dodge/Jeep P/N 05127382AA
- Chrysler/Dodge/Jeep P/N 68043742AA
- Daimler/Mercedes MB 236.12, 236.14, 236.41
- FORD/Lincoln/Mercury P/N XT-6-QSP or –DSP [SP]
- GM/GMC/Opel/Saturn AW1
- GM/GMC/Opel/Saturn P/N 88863400, 88863401
- Honda/Acura DW-1
- Honda 082000-9017 (ATF Type 3.1)
- Hyundai/Kia NWS-9638 T-5
- Hyundai/Kia P/N 040000C90SG
- Hyundai/Kia SP-IV / SPH-IV
- Jaguar/Land Rover Fluid 8432
- Land Rover P/N TYK500050, LR0022460
- Maserati P/N 231603
- Mazda FW 6A EL, FW 6AX EL
- Mazda FZ
- Mercon LV
- Mitsubishi ATF-J3 / Dia-Queen ATF-PA
- Nissan/Infinity Matic-S
- Porsche P/N 000 043 304 00
- Saab P/N 93 165 147 –AW-1
- Shell 3353/ 134 / M-1375.4 / 12108
- SP-IV / SPH-IV / SP-IV-RR
- Toyota Type WS (JWS 3324)
- Toyota/Lexus/Scion WS
- VW/Audi G 052 533, G 055 005 (-A,A2)
- VW/Audi G 055 540 (A2), G 060 162 (A1, A2, A6)
- ZF Lifeguard fluid 5/6

*meets the requirements of the OEM manufacturer

Bremöl GmbH – Am Hansator 5A – 28217 Bremen – Germany

Tel: +49-421-28020826

www.bremol.de

Mobile: +49-176-82370049

contact@bremol.de

Properties:

BREM GEAR ATF DEXRON IV

- Very high viscosity index
 - High load carrying capacity and extremely wear-reducing.
 - Twice the life of a normal ATF
 - No foam formation
 - High thermal stability
 - Soft switching operations even at low temperatures
 - Excellent viscosity-temperature behaviour
 - Excellent oxidation stability
 - Neutral towards common sealing materials
-

Application notes:

- **BREM GEAR ATF DEXRON IV**
- Excellent oxidation stability
- GM vehicles with Hydramatic transmissions from 2006
- Automatic automotive transmissions and torque converters
- Power steering
- Hydraulic systems

Observe manufacturer instructions!

TYPICAL PARAMETERS	METHODS	UNITS	BREM GEAR ATF DEXRON IV
Density at 15°C	DIN 12 185	kg/m ³	841
Viscosity at 40°C	DIN 51 659	mm ² /s	29.1
Viscosity at 100°C	DIN 51 659	mm ² /s	6.0
Viscosity Index (VI)	DIN ISO 2909	-	161
Pour point	DIN ISO 3016	°C	-48
Flash point COC	DIN ISO 2592	°C	218
Color	-	-	RED

* Meets the requirements of the OEM manufacturer.

The stated values may vary within the usual commercial range.