

BREM 5W-20 SP

- API SP
- ILSAC GF-6A

Recommendation*:

- Chrysler MS-6395, • GM dexos1™ Gen 3, • Ford WSS-M2C930-A, • Ford WSS-M2C945-A/-B1
- Ford WSS-M2C960-A, • Daihatsu , • Hyundai • Honda, • KIA, • Isuzu, • Lexus, • Mazda, • Nissan, • Subaru, • Suzuki, • Toyota,

Properties:

BREM 5W-20 SP is a HC-synthetic high-performance low viscosity engine oil for passenger cars. Base oils of the latest HC-synthesis technology and an innovative additive system tailored to this technology clearly exceed today's practical requirements. Excellent cold start behavior ensures optimum lubrication reliability in the cold running phase. Extreme loads and high temperatures are safely mastered. A targeted combination of active ingredients of the latest technology, which is specially adapted to the HC-synthetic components used, guarantees extremely high wear protection, protection against deposits and black sludge as well as high engine cleanliness

Thanks to its high fuel saving **BREM 5W-20 SP** contributes to the protection of the environment by reducing emissions.

Application notes:

BREM 5W-20 SP is specially designed for the most modern petrol engines, where the manufacturer prescribes such a low viscosity level.

Caution: Observe manufacturer 's instructions. The product has been developed exclusively for petrol engines and is not suitable for diesel engines.

TYPICAL PARAMETERS	METHODS	UNITS	BREM 5W-20 SP
Density at 15°C	DIN 51 757	kg/m ³	852
Viscosity at 40°C	DIN 51 562	mm ² /s	47.5
Viscosity at 100°C	DIN 51 562	mm ² /s	8.5
Viscosity at -30°C	DIN 51 377	mPa.s	4750
Viscosity Index (VI)	DIN ISO 2909	-	157
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	230
TBN DIN	ISO 3771	mg KOH/g	8.1

* Meets the requirements of the OEM manufacturer.

The stated values may vary within the usual commercial range.

Bremöl GmbH – Am Hansator 5A – 28217 Bremen – Germany

Tel: +49-421-28020826

www.bremol.de

Mobile: +49-176-82370049

contact@bremol.de