BREM DX1 5W-30 SP

API SP • ILSAC GF-6A

Recommendation*:
GM dexos1™ Gen 3, • GM 6094M, • Chrysler MS-6395, • Fiat 9.55535-CR1, • Ford WSS-M2C 929-A, • Ford WSS-M2C 946-A/-B1, • Ford WSS-M2C 961-A, • Daihatsu, • Honda, • Kia, • Isuzu, • Lexus, • Mazda, • Nissan, • Subaru • Suzuki, • Toyota , „where required“

Properties:
BREM DX1 5W-30 SP is an ultra high-performance engine oil. It is designed to meet the global gasoline engine specification of GM dexos1™ Gen 3.

BREM DX1 5W-30 SP has a new improved formulation to protect against damage caused by engine knocking in gasoline direct injection engines with and without turbocharging.
The composition of the oil minimizes the probability of early ignition (LSPI, Low Speed Pre-Ignition). Extended oil change intervals according to manufacturer ‘s instructions. Extreme loads and high temperatures are safely mastered.

BREM DX1 5W-30 can be used under all operating conditions and contributes to the protection of the environment by reducing pollutant emissions.

Application notes:
BREM DX1 5W-30 SP
is recommended for year-round use in petrol, ethanol (up to E85), propane and natural gas engines.
BREM DX1 5W-30 SP can also be used for all older ILSAC and API performance classes including ILSAC GF-5, API SN and SN PLUS. “The product is not suitable for diesel engines”.

TYPICAL PARAMETERS	METHODS	UNITS	BREM DX1 5W-30 SP
Density at 15°C	DIN 51 757	kg/m³	848
Viscosity at 40°C	DIN 51 562	mm²/s	60.9
Viscosity at 100°C	DIN 51 562	mm²/s	10.9
Viscosity Index (VI)	DIN ISO 2909	-	171
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	224
TBN DIN	ISO 3771	mg KOH/g	8.0

* Meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

Bremöl GmbH – Am Hansator 5A – 28217 Bremen – Germany
Tel: +49-421-28020826 **Mobile: +49-176-82370049**
www.bremol.de contact@bremol.de